

4 SPECIFICATION

Pultrusion Machine Specifications

Reciprocating Hydraulic with Vertical Clamping System

Model	ZSC-H-6	ZSC-H-12	ZSC-H-15	ZSC-H-20	ZSC-H-25
Pulling Capacity	6000kgf	12000kgf	15000kgf	20000kgf	25000kgf
Max. Clamping Space Width*Height	500*200(mm)	600*250(mm)	800*350(mm)	850*350(mm)	1000*400(mm)
Pulling Speed m/min	0.1~1.8(m)	0.1~1.5(m)	0.1~1.5(m)	0.1~1.2(m)	0.1~1.2(m)
Motor Power	3.7KW×2	5.5KW×2	7.5KW×2	7.5KW×2	11KW×2
Heating Zone	3	6	6-9	6-12	6-12
Puller Stroke in mm	650	650	800	800	800
Heating temperature range	0 ~ 400°C	0 ~ 400°C	0 ~ 400°C	0 ~ 400°C	0 ~ 400°C
Die Clamping Width in mm	590	680	850	860	860&1000
Overall Dimensions L*W*H	7.0*0.75*1.4(m)	8.5*0.9*1.6(m)	10.5*1.1*2.1(m)	11*1.15*2.1(m)	11.5*1.3*2.2(m)
Automatic Cut off Machine					
Cut Dimensions Width*Height	500*200(mm)	600*250(mm)	800*250(mm)	850*250(mm)	1000*250(mm)
Motor Kw.	3	3	3	3	3

5 PRODUCTS

